



Technical Specification Reynaers CF68 Bifold Doors

General Description	The Reynaers CF68 Bifold Door is one of the most reliable and durable Aluminium Bifold Doors available, having been tested to achieve the highest levels of performance and security. The master doors are fitted with multi-point locks and all intermediate doors are secured by high security shootbolts, meeting PAS 24 security levels and Secured By Design, making them incredibly secure.
Dimensions	Up to 2500mm High and 7000mm wide
Frame Depth front to back	68mm
Configurations	1 to 7 opening sashes
Weight	90kg per sash
Hardware	Multipoint Locking, Shootbolt Locking to Secondary Doors, Stainless Steel Rollers Lever Handles in Black, White or Satin Silver. Can be painted to match RAL.
Threshold	0-15mm Flush Threshold 9-30mm Low Threshold 23-44mm Double Weatherseal 23-74mm High Performance
Cill	150mm, 180mm and 220mm
Add-ons to Head	39mm; 52mm
Glass	12mm-55mm thick
Weathering	U-value to 1.1 – Triple Glazed Air Tightness: Class 4 Wind Resistance: C1/B3 Low Threshold, C2/B3 Double & High Performance Water Resistance: Class 5a (200 pa)
Security	PAS24, Secure by Design
Colours	Standard Colours: RAL7016 Anthracite Grey, RAL9005 Jet Black, RAL9016 Traffic White. Hundreds of other RAL Colours available